

## QUESTIONS FOR THE MRC 2015 PLAN REVIEW CE VIDEO CLASS

- 7) DRYER DUCTS SHALL BE SUPPORTED EVERY 4' AND SECURED IN PLACE.
- A) 2'
  - B) 4'
  - C) 6'
  - D) 8'
- 8) A KITCHEN HOOD THAT DISCHARGES A VOLUME OF EXHAUST GREATER THAN 400 CFM SHALL BE REQUIRED TO HAVE MAKE UP AIR TO COMPENSATE FOR THE AIR BEING EXHAUSTED BY THE HOOD. THE SPACE IS STILL REQUIRED TO MAINTAIN 65F IN THE HABITABLE SPACE.
- A) 65F
  - B) 68F
  - C) 70F
  - D) THE CODE DOES NOT REQUIRE A MINIMUM TEMPERATURE TO BE MAINTAINED IN HABITABLE AREAS OF A KITCHEN AS IT IS HEATED BY THE COOKING APPLIANCES.
- 9) A BOILER INSTALLATION WHICH HAS MULTIPLE BOILERS INSTALLED SHALL HAVE SHUT OFF VALVES LOCATED:
- A) ONLY ON THE FIRST BOILER RETURN LINE AND THE LAST BOILER SUPPLY LINE.
  - B) ONLY ON THE SECONDARY HEATING LOOP, THE PRIMARY LOOP DOES NOT REQUIRE SHUT OFF VALVES
  - C) THE ZONE VALVES FUNCTION AS THE REQUIRED SHUT OFF VALVES
  - D) ALL BOILERS SHALL HAVE A SHUT OFF VALVE ON THE SUPPLY AND RETURN LINES OF EACH BOILER.
- 10) A CLOTHES DRYER LOCATED IN A CLOSET SHALL HAVE A MINIMUM OF 100 SQ IN OF TRANSFER AIR?
- A) 100 SQ INCHES
  - B) 50 SQ INCHES
  - C) 200 SQ INCHES
  - D) NONE OF THE ABOVE

## QUESTIONS FOR THE MRC 2015 PLAN REVIEW CE VIDEO CLASS

- 1) THE INSPECTOR CAN ALLOW MODIFICATIONS FOR INDIVIDUAL CASES WHEN IT IS DEMONSTRATED THAT THE SITUATION MAKES FOLLOWING THE STRICT LETTER OF THE CODE IMPRACTICAL, EVEN IF IT MAY REDUCE THE HEALTH, LIFE AND FIRE SAFETY OF THE PROJECT?  
TRUE OR FALSE
- 2) THE CODE REQUIRES THE INDOOR HEATING TEMPERATURE TO BE A MINIMUM OF 68 F WHEN THE SPACE IS MEASURED 5' ABOVE THE FLOOR AND 2' IN FROM AN EXTERIOR WALL IN ANY HABITABLE SPACE.  
68 F - 3' AND 2'
- 3) A RESEDENTIAL BUILDING IS DEFINED IN THE CODE AS:  
ONE- AND TWO-FAMILY DWELLING UNITS AND MULTIPLE SINGLE-FAMILY DWELLINGS (TOWNHOUSES) AS WELL AS GROUP R-2, R-3 AND R-4 BUILDINGS THREE STORIES OR LESS IN HEIGHT ABOVE GRADE PLANE.  
TRUE OR FALSE
- 4) A SECONDARY DRAIN INSTALLED FOR AN AIR CONDITIONING SYSTEM LOCATED IN THE ATTIC SHALL DISCHARGE TO:  
A) AN APPROVED PLUMBING LOCATION IN A CONCEALED SPACE  
B) CAN BE CONNECTED TO THE PRIMARY DRAIN FOR THE A/C COIL.  
C) BOTH A AND B  
D) MUST BE INSTALLED TO DRAIN IN A CONSPICUOUS POINT OF DISPOSAL.
- 5) AN APPLIANCE LOCATED IN A GARAGE OR AREA OPEN TO THE GARAGE IS REQUIRED TO BE ELEVATED A MINIMUM OF 18" ABOVE THE FLOOR EXCEPT:  
A) WHEN THE HOMEOWNER PROMISES TO NOT STORE GASOLINE IN THE GARAGE.  
B) WHEN A FIRE EXTINGUISHER IS LOCATED WITHIN REACH OF THE WATER HEATER  
C) WHEN THE APPLIANCE IS LISTED AS "FLAMMABLE-VAPOR-IGNITION RESISTANT"  
D) NONE OF THE ABOVE
- 6) REFRIGERANT PIPING PROTECTION SHALL BE:  
A) ALLOWED TO BE SECURED DIRECTLY TO THE UNDERSIDE OF THE ROOF PLYWOOD OR OSB?  
B) CAN BE INSTALLED IN WALL CAVITIES WITHOUT NAIL PROTECTION AT THE UPPER AND LOWER PLATES?  
C) DOES NOT REQUIRE SUPPORTS IF THE PIPING IS LOCATED IN A CONCEALED ATTIC SPACE?  
D) NONE OF THE ABOVE